## Specifications

Specification	
Model	CS-C8C (1080P)
Camera	
Image sensor	1/2.7" Progressive Scan CMOS
Shutter Speed	Self-adaptive shutter
Lens	4mm@ F2.0, view angle:80° (Horizontal), 94°(Diagonal)
PT Angle	Pan: 352°, Tilt: 95°
Minimum Illumination	0.5 Lux @(F2.0, AGC ON), 0 Lux with IR
Lens Mount	M12
Day & Night	IR-cut filter with auto switch
DNR	3D DNR
WDR	Digital WDR
BLC	Supports
Night Vision	30m
Video & Audio	
Max. Resolution	1920 × 1080
Frame Rate	Max: 30fps; Self-Adaptive during network transmission
Video Compression	Smart H.265 / H.264
H.265 Type	Main Profile
Video Bit Rate	Ultra-HD; HD; Standard. Adaptive bit rate.
Audio Bit Rate	Self-Adaptive
Max. Bitrate	2Mbps
Network	
Wi-Fi Standard	IEEE802.11b, 802.11g, 802.11n
Frequency Range	2.4 GHz ~ 2.4835 GHz
Channel Bandwidth	Support 20MHz
Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
Transmission Rate	11b: 11Mbps,11g :54Mbps,11n :72Mbps
Wi-Fi Pairing	AP pairing
Protocol	EZVIZ cloud proprietary protocol
Interface Protocol	EZVIZ cloud proprietary protocol
Wired Network	RJ45 × 1 (10M/100M Adaptive Ethernet Port)
Function	
Smart Alarm	Al Human Detection
Customized Alert Area	Supports
Audio	Supports mic
General Function	Anti-Flicker, Dual-Stream, Heart Beat, Password Protection, Watermark
Storage	Missa CD and dat (May 2500)
Local Storage	Micro SD card slot (Max. 256G)
Cloud Storage	EZVIZ Cloud Storage
General Operating Conditions	2000 × 6000 ( 14°E to 112°E ) Humidity 050/ or loss ( non condension)
Operating Conditions  IP Grade	-30°C ~ 60°C ( 14°F to 113 °F ), Humidity 95% or less ( non-condensing)
Power Supply	DC 12V/1A
	MAX. 10W
Power Consumption Dimensions	
	158mm x 156mm x 149mm
Packaging Dimensions	
Weight	Product: 510g(1.12 lbs)  With Package: - g(- lbs)
	vvicii i dchage g(- ius)

